

A04



A01 HUS LTD

1 Industrialna Str.
3600 Lom, Bulgaria

A03 № 3130053394/ 13.08.2025

A02 Inspection certificate EN 10204 / 3.1 A05 HUS LTD

B01 Cold formed welded structural hollow sections of non-alloy and fine grain steels according EN 10219-2:2019

A08	Order №
A06	Customer SZATMARI KFT
A07	Invoice № 3130053394

B02	S235JRH	B10	length 6000 mm
B09	CFRHS		1.1 ; 1.4
B09	CFCHS		1.1 ; 1.4

TEST VERSION

B07		B08	13 440 m	B12		B13	
-----	--	-----	----------	-----	--	-----	--

B06 Bundle №	B08	B09	B10	B13	B07	Chemical composition %															B07	Mechanical properties								
					Heat №	C	Mn	Si	P	S	Al	Cu	Cr	Ni	Mo	Ti	V	Nb	N	CEV ₂	C00	C11	C12	C13	C14	C41	C43	C4 ₄	C50	
						x 100			x 1000			x 100			x 1000				x 100			Test №	ReH	Rm	A%	ReH	Impact	J		Certificate
																					MPa		MPa		/Rm	J/T-20°C	Average		№	
000464622798910	366,00 m	CFCHS 42.4x2.00	6000 mm		625246	14	38	1	11	25								6	21	413441-8	299	402						583928		
000466571898910	1350,00 m	CFRHS 20x20x2.00	6000 mm		143484	10	37	1	14	25								6	17	437305-10	279	378						557957		
000466701598910	1350,00 m	CFRHS 20x20x2.00	6000 mm		1024420	13	41	1	23	22								9	21	433069-8	265	446						549472		
000466623198910	1350,00 m	CFRHS 20x20x2.00	6000 mm		714583-9	11	38	2	23	25								6	19	437135-3	284	387						579301		
000466702798910	1350,00 m	CFRHS 20x20x2.00	6000 mm		1024420	13	41	1	23	22								9	21	433069-8	265	446						549472		
000466755598910	1350,00 m	CFRHS 20x20x2.00	6000 mm		624699	14	44	2	25	25								6	23	437019-13	294	431						579260		
000466508398910	1350,00 m	CFRHS 20x20x2.00	6000 mm		143484	10	37	1	14	25								6	17	437305-10	279	378						557957		
000466481298910	1350,00 m	CFRHS 20x20x2.00	6000 mm		724631	13	43	2	19	23								6	21	439827-4	299	412						581169		
000464443398920	294,00 m	CFRHS 60x60x4.00	6000 mm		514645-9	14	42	2	25	24								6	22	46455-3	260	422						629014		
000443258798910	1014,00 m	CFRHS 30x30x2.00	6000 mm		1024544	11	37	1	22	25								6	19	437931-4	270	392						558445		
000443259698910	1014,00 m	CFRHS 30x30x2.00	6000 mm		525116	12	40	1	25	23								6	20	45320-10	309	417						576064		
000443271198910	1014,00 m	CFRHS 30x30x2.00	6000 mm		1024544	11	37	1	22	25								6	19	437931-4	270	392						558445		
000463387198910 0	144,00 m	CFRHS 120x60x4.00	6000 mm		714508	14	36	2	17	25								6	22	46684-1	279	387						630165		

A04



A03 № 3130053394/ 13.08.2025

A02 Inspection certificate EN 10204 / 3.1 A05 HUS LTD

A01 HUS LTD

1 Industrialna Str.
3600 Lom, Bulgaria

B01 Cold formed welded structural hollow sections of non-alloy and fine grain steels according EN 10219-2:2019

000463390998910 0	144,00 m	CFRHS 120x60x4.00	6000 mm		515135-9	12	38	2	19	25							6	20	42195-15	279	402						933501
----------------------	----------	----------------------	---------	--	----------	----	----	---	----	----	--	--	--	--	--	--	---	----	----------	-----	-----	--	--	--	--	--	--------

D02 Non-destructive testing - passed.

Z02



Z03 Director Branch Lom
N.Dechev
13.08.2025 г. 0:00:00 ч.

Z04



www.husltd.com

1938

A05 TT

D01 The test has been performed on the provided products and the results are satisfactory.

17

1938-CPR-0285/2

Z01 The producer declares that the product is according to the customer's order.

Z05 Without any post heat treatment; with shape, dimensions and tolerances according EN 10219-2; performance characteristics according appendix ZA.1 of the product standart. Function - for steel structures and combined steel and reinforced concrete structures.

Z06 Claims are allowed within 14 days from product receipt. In order to consider a claim, the customer must provide a quality inspection control document and a marking on the claimed goods. Claims associated with unloading and storage of the goods will not be accepted.

Z07 Declaration of performance № 3130053394 HUS CFRHS S235JRH / 2025

INSTRUCTIONS FOR USE

COLD FORMED STRUCTURAL HOLLOW SECTIONS OF NON-ALLOY AND FINE GRAIN STEELS

1. Application

The sections are suited for metal and reinforced concrete constructions.

2. Instructions for design and use

The following should be noted when designing, choosing the properties and the application of the section in any metal or reinforced concrete construction:

- Size of the section
- Steel grade / chemical composition and physical properties/,
- Weight of one linear meter.

3. Packing

The sections are arranged in bundles fully lined with a maximum weight of 4 000 kg. The bundle is covered on 7 places with metal packaging tape.

4. Marking

Each package bears a label with barcode and information about the size and number of sections in the package, the total length of the packet.

5. Transportation and unloading

Recommended way of transportation - covered transportation vehicles with general purpose which prevent direct climate impact.

An inspection is to be made during loading/unloading stage to confirm that packing and packing strips are present and unharmed. When these are torn and missing any loading/unloading and transportation is to be resumed only after repairing the same.

6. Storage

Store in indoor dry storage areas.

7. Operational Safety

The company's instructions and regulations on safety are to be observed when working with hollow sections. Loading and unloading can be carried out by qualified persons with faulty equipment and personal protective equipment.

8. Waste and environmental protection

The non-utilized remains as a result of the intended use of the hollow sections are to be stored and used for auxiliary work or to be submitted for scrap.

The raw material – a metal sheet and the produced cold formed structural hollow sections do not contain any substances harmful to human health, are non-toxic and do not pollute the environment.

13.08.2025

64A Plovdiv-Sever str., 4027 Plovdiv, Bulgaria, tel: +359 32/233000, fax: +359 32/233070, e-mail: office@husltd.com

Ring road, Plovdiv, tel/fax +359 32/690680, tel: +359 32/233045

64 Iliyantsi bul, 1220 Sofia, tel/fax: +359 2/9317035, tel: +359 32/233081, tel: +359 32/233082, tel: +359 32/233083

Botunets, Seslavtsi Qr., 1808 Sofia, tel: +359 2/4461242; tel: +359 2/4461243; tel: +359 2/4461244;

West Industrial Park, 9000 Varna, tel: +359 52/812982

Sarafovo district, 8016 Burgas, tel/fax: +359 56/810580, tel/fax: +359 56/810250

1 Industrial str., 3600 Lom, tel: +359 971/87011

3 Matej Stojkov str., 7000 Ruse, tel: +359 82/9269524

Industrial Zone, 9160 Devnya, tel: +359 886/2488866

№ 3130053394 HUS CFCHS S235JRH /2022

1. Unique identification code of the product type: CFCHS – S235JRH
diameter up to 165.1 mm., thickness up to 5.00 mm.
2. Intended use/es: Cold formed welded structural hollow section of non-alloy and fine grain steel, without subsequent heat treatment, shape dimensions and tolerances in accordance with БДС EN 10219-2:2006. Applied for load-bearing structural construction works (construction works covers building and civil engineering works)
3. Manufacturer: HUS Ltd 4027 Plovdiv, Bulgaria, 64A Plovdiv Sever Str.
HUS Ltd Manufacturing plant 3600 Lon, Bulgaria, 1 Industrialna Str.
www.husltd.com
4. Authorized representative: Not relevant
5. System/s or AVCP: System 2+
- 6 a. Harmonised standard: EN 10219-1:2006
Notified body: Институт по механика-БАН, A person for assessment of conformity of construction products license № CPR 02-NB 1938/24.02.2014 на МРРБ. Identification number 1938 from EC register.
- 6 b. European Assessment Document: Nor relevant (see 6a)
European Technical Assessment (ETA):
7. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Tolerance on dimensions and shape	Correspond	БДС EN 10219-2:2006 item 6.
Material grade – Steel S235JRH , number 1.0039		
Elongation A ^d , %	Specified thickness , mm	БДС EN 10219-1:2006 item 6.7.1 table A.3
	≤3 >3 ≤10	
	>17 ^d >24 ¹	
Tensile strength R _m , MPa	Specified thickness , mm	БДС EN 10219-1:2006 item 6.7.1 table A.3
	≤3 >3 ≤10	
	360 - 510 360 - 510	
Yield strength R _{eH} , MPa	Specified thickness , mm	БДС EN 10219-1:2006 item 6.7.1 table A.3
	≤3 >3 ≤10	
	≥ 235 ≥ 235	
Weld ability (Chemical composition)	CEV ≤0,35	БДС EN 10219-1:2006 item 6.6.table A.2 and item 6.8.1.
Impact strength, J	Specified thickness , mm	БДС EN 10219-1:2006 item 6.7.2 table A.3
	<6 ≥6 ≤10	
	NPD 27	
Durability	NPD	БДС EN 10219-1:2006 item 6.8.2, table ZA.1

d For thicknesses < 3 mm see 9.2.2

1 For thicknesses > 3 mm and section sizes D/T <15 the minimum elongation is reduced by 2.

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

Standart EN 10219-1/2:2006

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation EU 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Director Branch Lom, N.Dechev

Lom, 13.08.2025

Information about the environment and safety (REACH)

Products are article within the meaning of Article 3 of the EU regulation № 1907/2006 REACH. The products do not contain substances which can be released from the device under normal and foreseeable conditions of use.

1. Unique identification code of the product type: CFRHS – S235JRH
2. Intended use/es: Cold formed welded structural hollow section of non-alloy and fine grain steel, without subsequent heat treatment, shape dimensions and tolerances in accordance with БДС EN 10219-2:2006. Applied for load-bearing structural construction works (construction works covers building and civil engineering works)
3. Manufacturer: HUS Ltd 4027 Plovdiv, Bulgaria, 64A Plovdiv Sever Str.
HUS Ltd Manufacturing plant 3600 Lon, Bulgaria, 1 Industrialna Str.
www.husltd.com
4. Authorized representative: Not relevant
5. System/s or AVCP: System 2+
- 6 a. Harmonised standard: EN 10219-1:2006
Notified body: Институт по механика-БАН, A person for assessment of conformity of construction products license № CPR 02-NB 1938/24.02.2014 на МРРБ. Identification number 1938 from EC register.
- 6 b. European Assessment Document: Nor relevant (see 6a)
European Technical Assessment (ETA):
7. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Tolerance on dimensions and shape	Correspond	БДС EN 10219-2:2006 item 6.
Material grade – Steel S235JRH , number 1.0039		
Elongation A^d , %	Specified thickness , mm	БДС EN 10219-1:2006 item 6.7.1 table A.3
	≤3 >3 ≤10	
	>17 ^d >24 ¹	
Tensile strength R_m , MPa	Specified thickness , mm	БДС EN 10219-1:2006 item 6.7.1 table A.3
	≤3 >3 ≤10	
	360 - 510 360 - 510	
Yield strength R_{eH} , MPa	Specified thickness , mm	БДС EN 10219-1:2006 item 6.7.1 table A.3
	≤3 >3 ≤10	
	≥ 235 ≥ 235	
Weld ability (Chemical composition)	CEV ≤0,35	БДС EN 10219-1:2006 item 6.6.table A.2 and item 6.8.1.
Impact strength, J	Specified thickness , mm	БДС EN 10219-1:2006 item 6.7.2 table A.3
	<6 ≥6 ≤10	
	NPD 27	
Durability	NPD	БДС EN 10219-1:2006 item 6.8.2, table ZA.1

d For thicknesses < 3 mm see 9.2.2

1 For thicknesses > 3 mm and section sizes (B+H)/2T <12,5 the minimum elongation is reduced by 2.

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

Standart EN 10219-1/2:2006

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation EU 305/2011, under the sole responsibility of the manufacturer identified above.

Lom, 13.08.2025

Signed for and on behalf of the manufacturer by: Director Branch Lom, N.Dechev

Information about the environment and safety (REACH)

Products are article within the meaning of Article 3 of the EU regulation № 1907/2006 REACH. The products do not contain substances which can be released from the device under normal and foreseeable conditions of use.